

# IDKA-XXXXXXXX VERSAKEY POS Keyboard Specifications

## Electrical

Power Requirement: +5.0 VDC  $\pm$ 10%, 60ma Max.  
Industry Requirements: FCC class B and CE.

## Environmental

Drop: 610 mm (24") Drop: 1 corner, 2-sidelines, 3-sides.  
Vibration: 60 Hz/sec 3 mm amplitude X,Y,Z each axis at 2 hours.  
Operating Temperature: 0°C to 40°C (32°F to 104°F).  
Storage Temperature: -20°C to 40°C (-4°F to 104°F).

## Mechanical

Keyswitch  
Total Travel: 4.0 + 0.5 mm.  
Operating Force: 50 + 7g.  
Keyboard  
Color: Black or Beige.  
Size: 469.9 mm (L) x 203.9 mm (W) x 42.8 mm (H).  
Material: High Impact PS, Meets flammability spec. UL94HB.  
Cable Information  
Jacket Material: PVC jacket with Aluminum Shielding.  
Length: 1.5 M (5ft.) Overall.  
PC Connector: PS/2 or USB.

## Reliability

Keyboard Operating Life: 20,000,000 keystrokes.  
MagStripe Reader Life: 1,000,000 cycles.  
ESD Immunity: 0KV to 8 kV min, without data loss.  
8KV to 15 kV min, will function after reset.  
MTBF: More than 60,000 hours.  
Conformance: ISO 7811 1-6.  
Magnetic Stripe Formats: ISO 7811, AAMVA, and CA DMV.  
Swipe Speed: 3 to 60 inches per second, bi-directional.  
Card Thickness: .015 to .045 inches.  
Indicators: Beeper.

### B & C Data Systems

P.O. Box 1369  
Shady Cove, OR 97539  
(541) 601-8282 Fax: (541) 878-8110  
Visit us at [www.bcdata.com](http://www.bcdata.com)